

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

Supplier: Paul H. Gesswein & Co., Inc., 201 Hancock Ave., Bridgeport, CT 06605
Phone: 203-366-5400, FAX 203-366-3953
Emergency phone number: CHEMTEL - 800-255-3924

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : GALVEX 17.30 SUPRA USA
Product code : 8515289, 8515292, 8515294, 8515307, 8515304

1.2. Relevant identified uses of the substance or mixture and uses advised against

Precision Cleaning for Ultrasonic processes

1.3. Details of the supplier of the safety data sheet

Registered company name : NGL CLEANING TECHNOLOGY SA.
Address : Chemin de la Vuarpillière 7.CH-1260.NYON.SUISSE.
Telephone : 00.41.(0).22.365.46.66. Fax : 00.41.(0).22.361.81.03.
ngl@ngl-group.com
www.ngl-group.com

1.4. Emergency telephone number : Urgence 145 24h/24h.

Association/Organisation : Centre Suisse Antipoison - Freiestrasse 16 - CH-8032 Zurich-.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1B (Skin Corr. 1B, H314).

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Skin irritation (Xi, R 38).

Serious eye damage (Xi, R 41).

May produce an allergic reaction.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :

DANGER

Product identifiers :

EC 268-935-9

EC 287-494-3

AMIDES, C8-18 AND C18-UNSATD., N,N-BIS(HYDROXYETHYL)
BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

603-030-00-8	2-AMINOETHANOL
603-071-00-1	2,2'-DIHYDROXYDIETHYLAMINE
Additional labeling :	
EUH208	Contains DIETHYLENETRIAMINE. May produce an allergic reaction.
Hazard statements :	
H314	Causes severe skin burns and eye damage.
Precautionary statements - Prevention :	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see ... on this label).
P363	Wash contaminated clothing before reuse.
Precautionary statements - Storage :	
P405	Store locked up.
Precautionary statements - Disposal :	
P501	Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 0053 CAS: 68155-07-7 EC: 268-935-9 AMIDES, C8-18 AND C18-UNSATD., N,N-BIS(HYDROXYETHYL)	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318	Xi Xi;R38-R41		2.5 \leq x % < 10
INDEX: 0026 CAS: 57-55-6 EC: 200-338-0 REACH: 01-2119456809-23-xxxx PROPANE-1,2-DIOL			[1]	2.5 \leq x % < 10
INDEX: 0064 CAS: 85536-14-7 EC: 287-494-3 BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314	C C;R34 Xn;R22		2.5 \leq x % < 10

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

INDEX: 0077 CAS: 7320-34-5 EC: 230-785-7 TETRAPOTASSIUM PYROPHOSPHATE	GHS07 Wng Eye Irrit. 2, H319	Xi Xi;R36		2.5 <= x % < 10
INDEX: 603-030-00-8 CAS: 141-43-5 EC: 205-483-3 2-AMINOETHANOL	GHS05, GHS07 Dgr Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314	C C;R34 Xn;R20/21/22	[1]	2.5 <= x % < 10
INDEX: 603-071-00-1 CAS: 111-42-2 EC: 203-868-0 2,2'-DIHYDROXYDIETHYLAMINE	GHS08, GHS05, GHS07 Dgr Acute Tox. 4, H302 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Dam. 1, H318	Xn Xn;R48/22-R22 Xi;R38-R41	[1]	2.5 <= x % < 10
INDEX: 0120 CAS: 139-89-9 EC: 205-381-9 HYDROXYETHYLETHYLENDIAMINTRIAC ETIC ACID, TRISODIUMSALT	GHS07 Wng Eye Irrit. 2, H319	Xi Xi;R36		0 <= x % < 2.5
INDEX: 612-058-00-X CAS: 111-40-0 EC: 203-865-4 DIETHYLENETRIAMINE	GHS05, GHS07 Dgr Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317	C C;R34 Xn;R21/22 Xi;R43	[1]	0 <= x % < 2.5

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

Fire prevention :

Handle in well-ventilated areas.
Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Stock between 5 °C and 40°C in a dry, well ventilated place

Storage

Keep the container tightly closed in a dry, well-ventilated place.
The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
141-43-5	2.5	1	7.6	3	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
141-43-5	3 ppm	6 ppm	-	-	-
111-42-2	2 mg/m3	-	-	-	-
111-40-0	1 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
141-43-5	2 ml/m3	5,1 mg/m3	2(I)	DFG, H, Y

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
141-43-5	1	2.5	3	7.6	-	49, 49 Bis
111-42-2	3	15	-	-	-	49.49 Bis
111-40-0	1	4	-	-	AC	49.49 Bis

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
57-55-6	150 ppm	-	-	-	-
141-43-5	3 ppm	6 ppm	-	-	-
111-40-0	1 ppm	-	-	-	-

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Suitable type of protective boots :

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Viscous liquid.
Color:	yellow
Odour:	characteristic

Important health, safety and environmental information

pH :	11.20 .
	Slightly basic.
pH (aqueous solution) :	10.2
Boiling point/boiling range :	Not specified.

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	1.056
Miscibility :	100%
Water solubility :	Dilutable.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.
% VOC :	0

9.2. Other information

VOC (g/l) :	0.000
-------------	-------

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 111-42-2 : IARC Group 2B : The agent is possibly carcinogenic to humans.

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

07 06 04 * other organic solvents, washing liquids and mother liquors

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

14.1. UN number

3267

14.2. UN proper shipping name

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(2-aminoethanol, diethylenetriamine)

14.3. Transport hazard class(es)

- Classification :



8

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	II	8	80	1 L	274	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	II	1 L	F-A,S-B	274	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :



Irritant

GALVEX 17.30 SUPRA USA - GX-1730-SUSA

Contains :

Contains 612-058-00-X DIETHYLENETRIAMINE. May produce an allergic reaction.

Risk phrase :

R 38 Irritating to skin.
R 41 Risk of serious damage to eyes.

Safety phrase :

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S 39 Wear eye/face protection.
S 36/37 Wear suitable protective clothing and gloves.
S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S 60 This material and its container must be disposed of as hazardous waste.

Title for H, EUH and R indications mentioned in section 3 :

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure .
R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R 21/22 Harmful in contact with skin and if swallowed.
R 22 Harmful if swallowed.
R 34 Causes burns.
R 36 Irritating to eyes.
R 38 Irritating to skin.
R 41 Risk of serious damage to eyes.
R 43 May cause sensitisation by skin contact.
R 48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS05 : Corrosion