



## **SAFETY DATA SHEET**

## SECTION 1 / Identification

Product Name: Veggie Compound White Ice

**Product Number: 2151800, 2151801** 

Supplier Information

Paul H. Gesswein & Co., Inc.

201 Hancock Ave., Bridgeport, CT 06605 Phone: 203-366-5400, FAX: 203-366-3953

email: info@gesswein.com, www.gesswein.com

Emergency phone number: CHEMTELL - 800-255-3924

Date: 5/11/2015

## SECTION 2: Hazard(s) Identifications

Buffing Compounds as shipped do not present a hazard.

Buffering operations may cause lint and abrasives to become airborne. Proper ventilation and

respirator recommended.

Signal Word:

Warning

# SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Saturated Fatty Acids	57-11-4	less than 2%
Silica	1317-95-9	less than70%
Petrolatum	8 009-03-8	less than 35%
Limestone	1317-65-3	less than 25%

#### **SECTION 4: First Aid Measures**

Ingestion: If swallowed - seek medical attentionInhalation: Move to a fresh air environment

**Eye Contact:** Flush thoroughly with water and call physician **Skin Contact:** Remove dust from skin with warm water and soap

## **SECTION 5: Firefighting measures**

Flash Point (method used): 350° F min (CoC)

LEL: N/A

Extinguishing Media: CO<sub>2</sub> Dry Chemical

Special Fire Fighting Instructions: Use Air packs - Treat as grease fire

Unusual Fire and Explosion Hazards: Dense smoke

Flammable Limits: No Data

**UEL:** N/A

#### **SECTION 6: Accidental release measures**

If material is spilled or released - Shovel and mop up. Normal clean up procedures per State and local laws. Care taken to avoid dust from becoming airborne.

# **SECTION 7: Handling and Storage**

Do not store near direct heat sources - Store in cool, dry area

No other precautions apply

## **SECTION 8: Exposure controls/personal protection**

Hazardous Component	OSHA PEL	ACGIH / TLV
Saturated Fatty Acids	5mg ./m³	5mg ./m³
Silica	.1mg ./m³	.1mg ./m³
Petrolatum	15mg ./m³	5mg ./m³
Limestone	15mg ./m³	10mg ./m³

Special: None

**Mechanical (General):** To maintain employee below permissible limits.

Ventilation: Local Exhaust / Fan or Open Window

**Respiratory Protection**: OSHA/MOHA approved dust mask / respirator

Gloves: Yes

**Eye Protection**: Safety Glasses or Goggles **Other**: Long sleeve protective clothing

### **SECTION 9: Physical and chemical properties**

Boiling Point: > 450°FSpecific Gravity: 1.5 to 3.5Vapor Pressure (mm Hg):N/AMelting Point: 140°FVapor Density:N/AEvaporation Rate: N/ASolubility in Water:Insoluble(Butyl Acetate= 1)

**Appearance & Odor:** Bar form - Off white

### **SECTION 10: Stability and Reactivity**

Stability: Yes Incompatibility: N/A

Hazardous Decomposition of By-Products: N/A

Hazardous Polymerization: Will not occur

Conditions to Avoid: N/A

## **SECTION 11: Toxological Information**

Route(s) of Entry: Inhalation: Yes Skin: No Ingestion: No Health Hazards (Acute & Chronic - Buffing operations may cause lint and abrasives to become airborne

We recommend respirator and ventilation.

Effects of overexposure: Irritation to eyes, ears, nose and throat

Carcinogenicity: N/A NTP: N/A

IARC Monographs: No OSHA Regulated: No

### **SECTION 12: Ecological information (Non-Mandatory)**

Ecotocity: none

#### SECTION 13: Disposal considerations (Non-Mandatory)

Per State and Local Law

### **SECTION 14: Transport Information (Non-Mandatory)**

Not regulated as dangerous goods

#### SECTION 15: Regulatory Information (Non-Mandatory)

None

### **SECTION 16: Other Information (Non-Mandatory)**

Revision Date: 05/11/2015

**Revision Summary:** 

Update all sections - GHS / SDS compliance

Revised By: A.Battle