

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A

Alternate Names

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Technical Data Sheet.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

F. E. Knight Inc.
120 Constitution Blvd.,
Franklin, MA 02038. USA

Emergency

CHEMTREC (USA)

(800) 424-9300

24 hour Emergency Telephone No.

Chem-Tel: 1-800-255-3924

Customer Service: F. E. Knight Inc.

508-520-1666 or 617-969-5399

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Acute Tox. 4;H332	Harmful if inhaled.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Resp. Sens. 1;H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2;H351	Suspected of causing cancer.
STOT SE 3;H335	May cause respiratory irritation.
STOT RE 2;H373	May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014



Danger

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Polymeric Diphenylmethane Diisocyanate CAS Number: 0009016-87-9	25 - 50	Acute Tox. 4;H332 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Sens. 1;H317 Resp. Sens. 1;H334	[1]
Diphenylmethanediisocyanate CAS Number: 0000101-68-8	10 - 25	Carc. 2;H351 Acute tox. 4;H332 STOT RE 2;H373 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Resp. Sens. 1;H334 Skin Sens. 1;H317	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Primary Route(s) of Entry: Inhalation, skin or eye absorption.

Eye: May cause moderate eye irritation.

Skin: Exposure may cause skin irritation, staining, or sensitization.

Ingestion: Single oral dose toxicity is low. May cause nausea, vomiting, and diarrhea.

Inhalation: At room temp., vapors are minimal. Vapors or aerosols (e.g., generated during heating or spraying) may cause respiratory irritation. May cause respiratory sensitization in susceptible individuals. For individuals sensitized to MDI, exposure may result in allergic respiratory reactions (e.g., coughing, difficulty breathing).

Chronic Effects: Repeated overexposure to MDI may cause respiratory and dermal sensitization.

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

See section 2 for further details.

Inhalation

Harmful if inhaled. May cause allergy or asthma symptoms of breathing difficulties if inhaled.

Eyes

Causes serious eye irritation.

Skin

May cause an allergic skin reaction. Causes skin irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Possibly isocyanate vapor, carbon monoxide, nitrogen oxides, and traces of hydrogen cyanide.

Composition products may include MDI vapor, nitrogen oxides, isocyanates, carbon monoxide, carbon dioxide, and unidentified toxic and irritating compounds.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Firefighters wear SCBA and full-body protective suit. Solid stream of water into hot product may cause violent steam generation or eruption. Dense smoke is formed when product burns. Use water to cool hot containers

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. ----

6. Accidental release measures

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Clear non-emergency personnel from the area. Extinguish sources of ignition. Put on protective equipment (see Section 8). Contain spill to minimize environmental contamination. Absorb spilled material with an inert absorbent. Collect and containerize material. Do not seal containers of spill residue since carbon dioxide is generated upon contact with moisture and dangerous pressure buildup can occur. Neutralize contaminated floor area with a mixture of water (90%), ammonia (3-8%) and detergent (2%). Clean floor before material reacts with moisture in the air and forms a difficult to remove rubber.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Precautions should be taken to minimize exposure to atmospheric humidity or water as carbon dioxide may be formed which, in closed containers can result in pressurization. Care should be taken when re-opening partly used containers.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons applying this preparation.

Incompatible materials: Avoid contact with water, acids, bases, alcohols, strong oxidizers, and some metals (e.g., aluminum, brass, copper). Reaction with water generates carbon dioxide, and results in heat and pressure buildup in closed systems.

Store indoors at temperatures > 75°F and < 105°F. Store in original, unopened container. Protect from atmospheric moisture and water, since MDI reacts with water to form CO₂ leading to potentially dangerous pressure build up in sealed.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

Exposure

CAS No.	Ingredient	Source	Value
0000101-68-8	Diphenylmethanediisocyanate	OSHA	C 0.2 mg/m ³ (0.02 ppm)
		ACGIH	TWA: 0.005 ppm Ceiling: 0.01 ppmSkin, S
		NIOSH	TWA 0.05 mg/m ³ (0.005 ppm) C 0.2 mg/m ³ (0.020 ppm) [10-minute]
		Supplier	No Established Limit
0009016-87-9	Polymeric Diphenylmethane Diisocyanate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000101-68-8	Diphenylmethanediisocyanate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0009016-87-9	Polymeric Diphenylmethane Diisocyanate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Protective safety glasses recommended.

Skin

Wear overalls to keep skin contact to a minimum. Chemical splash goggles, protective clothing, and impervious rubber gloves are recommended.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Brown Clear Liquid
Odor	Mild
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	No Data
Flash Point	400 F (estimated)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Negligible
Vapor Density	Not Measured
Specific Gravity	Approximately 1.1, at 25 C, g/cc
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Solubility in Water	Insoluble forms CO2

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Moisture and temperatures < 75 °F and > 95°F to ensure product integrity.

10.5. Incompatible materials

Avoid contact with water, acids, bases, alcohols, strong oxidizers, and some metals (e.g., aluminum, brass, copper).

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

Reaction with water generates carbon dioxide, and results in heat and pressure buildup in closed systems.

10.6. Hazardous decomposition products

Possibly isocyanate vapor, carbon monoxide, nitrogen oxides, and traces of hydrogen cyanide.

11. Toxicological information

Acute toxicity

Based on the properties of the isocyanate content of this product, respiratory exposure may cause acute irritation and/or sensitisation of the respiratory system resulting in asthmatic symptoms, wheezing and a tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to airborne concentrations of isocyanates well below the occupational exposure limit. Repeated exposure may lead to permanent respiratory disability.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Polymeric Diphenylmethane Diisocyanate - (9016-87-9)	49,000.00, Rat - Category: NA	9,400.00, Rabbit - Category: NA	No data available	No data available	No data available
Diphenylmethanediisocyanate - (101-68-8)	4,700.00, Rat - Category: 5	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive toxicity	---	Not Applicable

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Polymeric Diphenylmethane Diisocyanate - (9016-87-9)	Not Available	Not Available	Not Available
Diphenylmethanediisocyanate - (101-68-8)	Not Available	129.70, Daphnia magna	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Toxic fumes may be generated upon incineration.

14. Transport information

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2 D2A
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes
EPCRA 311/312 Chemicals and RQs (lbs):	Diphenylmethanediisocyanate (5,000.00)
EPCRA 302 Extremely Hazardous : (No Product Ingredients Listed)	
EPCRA 313 Toxic Chemicals:	Diphenylmethanediisocyanate Polymeric Diphenylmethane Diisocyanate
Proposition 65 - Carcinogens (>0.0%): (No Product Ingredients Listed)	
Proposition 65 - Developmental Toxins (>0.0%): (No Product Ingredients Listed)	
Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)	
Proposition 65 - Male Repro Toxins (>0.0%):	

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part A



SDS Revision Date:

11/03/2014

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Diphenylmethanediisocyanate
Polymeric Diphenylmethane Diisocyanate

Penn RTK Substances (>1%):

Diphenylmethanediisocyanate

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: The information contained herein is considered accurate; however, F .E. Knight, Inc. makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.

End of Document

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B
Alternate Names Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name F. E. Knight Inc.
120 Constitution Blvd.,
Franklin, MA 02038. USA

Emergency

24 hour Emergency Telephone No. Chem-Tel: 1-800-255-3924 or 617-969-5399
Customer Service: F. E. Knight Inc. 508-520-1666

2. Hazard identification of the product

2.1. Classification of the substance or mixture

No applicable GHS categories.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

No applicable GHS categories.

[Prevention]:

No GHS prevention statements

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

[Response]:

No GHS response statements

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Trade secret blend containing Polyester Polyol CAS Number: Proprietary	75 - 100		[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

Overview

Eye: May cause moderate eye irritation.

Skin: Exposure may cause skin irritation and/or redness.

Ingestion: Toxic by ingestion (contains 0.1% of a toxic mercury compound. May cause gastrointestinal discomfort if ingested.

Inhalation: At room temp., vapors are minimal and material is not expected to be an inhalation hazard.

Chronic Effects: Contains 0.1% of an aryl mercury compound. Long-term overexposure to mercury has been associated with central nervous system, digestive system, and kidney disorders.

Carcinogenicity: Contains 0.1% of an aryl mercury compound. Long-term overexposure to mercury has been associated with central nervous system, digestive system, and kidney disorders.

See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water fog

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Potentially oxides of carbon, organic acids, mercury vapor, and other unidentified irritating or toxic compounds.

5.3. Advice for fire-fighters

Hazardous Combustion Products: Likely to include carbon monoxide, carbon dioxide, mercury vapor, and unidentified toxic and irritating compounds.

Other Information: Firefighters wear protective gear and self-contained breathing apparatus (SCBA). Use water to cool hot containers.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

Clear non-emergency personnel. Put on protective equipment. Remove sources of ignition. Contain spill to minimize environmental contamination. Absorb spilled material with non-reactive absorbent such as sawdust, vermiculite, or sand. Collect and containerize spill material. Dispose of in accordance with federal, state and local regulations.

7. Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use in adequately ventilated area. Do not eat, drink or smoke in work area. Wash hands after handling.

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: oxidizers

Store indoors. Do not exceed 120°F. Store in original container tightly closed.

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

There are no ingredients in this product with exposure limits

8.2. Exposure controls

Respiratory In the absence of good ventilation, or if vapors or mists are generated (e.g., through heating or spraying), use respirator equipped with organic vapor cartridges. In emergency situations, use SCBA.

Eyes Protective safety glasses recommended.

Skin Wear overalls to keep skin contact to a minimum. Chemical splash goggles, protective clothing, and impervious rubber gloves are recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance

Pink opaque Liquid

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

Odor	Mild
Odor threshold	Not Measured
pH	NA
Melting point / freezing point	NA
Initial boiling point and boiling range	No data
Flash Point	350 F (estimated)
Evaporation rate (Ether = 1)	NA
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: NA Upper Explosive Limit: NA
Vapor pressure (Pa)	NA
Vapor Density	NA
Specific Gravity	1.4 @ 25 C, G/CC
Solubility in Water	Negligible
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	NA
Decomposition temperature	NA
Viscosity (cSt)	NA
VOC %	NA

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid moisture and temperatures > 80F.

10.5. Incompatible materials

Oxidizers

10.6. Hazardous decomposition products

Potentially oxides of carbon, organic acids, mercury vapor, and other unidentified irritating or toxic compounds.

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

11. Toxicological information

Acute toxicity

There are no ingredients in this product with known toxicity data.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user			
	No further information		

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification Not Regulated

US EPA Tier II Hazards

Fire:No

Sudden Release of Pressure:No

Reactive:No

Immediate (Acute):No

Delayed (Chronic):No

EPCRA 311/312 Chemicals and RQs:
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous :
Proprietary aryl mercury compound

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

EPCRA 313 Toxic Chemicals:

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

Proprietary aryl mercury compound

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

(No Product Ingredients Listed)

Penn RTK Substances (>1%) :

(No Product Ingredients Listed)

Safety Data Sheet

Castaldo® LiquaCast® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

12/05/2014

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

Not Applicable

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: The information contained herein is considered accurate; however, F .E. Knight, Inc. makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.

End of Document